

MATERIAL SAFETY DATA SHEET

SECTION I - NAME AND PRODUCT

MANUFACTURER'S NAME WOOSTER PRODUCTS INC			REVISION DATE August 1, 2003 (Supercedes all earlier MSDS)	
ADDRESS (Street, City, State, and Zip Code) 1000 Spruce St, PO Box 6005, Wooster, OH 44691 Ph#330-264-2844			Emergency Telephone No. Chemtrec: 1-800-424-9300	
TRADE NAME WP70 PART B - ALL COLORS				
C.A.S Number NONE	Sub Risk	D.O.T. Hazard Class 8	Packing Group: III	HMIS Code: 2 1 0 F
I.D. UN 1760	MFAG:		Proper Shipping Name Trade name WP70 "B" Corrosive Liquid N.O.S. (Polyalkyl amine)	

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENTS	CAS#	WEIGHT %	EXPOSURE LIMITS	
			ACGIH/TLV	OSHA/PEL
Trade Secret				
Aliphatic Amine				
NJTSRN - EP947 Part B				
Bisphenol A (xx)	80-05-07			

xx Denotes Section 313 Toxic Chemical

xxx All ingredients in this product are listed in the T.S.C.A. inventory.

SECTION III - PHYSICAL DATA

Boiling Range:	N/A	Vapor Density:	Liquid Density:	Heavier than water	
Evap. Rate(n-Butyl Acetate = 1)	N/A	Percent Volatile By Volume:	0.0%	Weight Per Gallon:	9.43 lbs
Appearance:	Liquid				

SECTION IV - FIRE AND EXPLOSION DATA

Flammability Class:	Flash Point:	>200°F/PMCC	LEL: Not Est.	UEL: Not Est.
Extinguishing Media: Dry Chemical, foam, carbon dioxide, water spray				
Special Fire Fighting Procedures: Use full protective clothing and a positive pressure self contained breathing apparatus. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coat, gloves and rubber boots), including a positive NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.				

SECTION V - HEALTH, FIRST AID AND MEDICAL DATA

3002

PRIMARY ROUTE(S) OF ENTRY	EFFECTS OF OVEREXPOSURE	FIRST AID AND MEDICAL INFORMATION
Inhalation	The acute inhalation LC50 is 1000 ppm in rats after an 8 hour inhalation exposure. Acute overexposure: Temporary irritation to mucous membranes of the nose and mouth may result from excessive dust. Inhalation of the vapors may produce respiratory irritation, coughing, labored breathing, dizziness, and respiratory failure.	Remove person to fresh air. Give oxygen if breathing is difficult. Obtain immediate medical attention.
Eye Contact	Corrosive to eyes. Burns of the eyes may cause blindness. Contact of diluted product with the eyes or skin quickly causes severe irritation and pain and may cause burns, necrosis and permanent injury.	Flush thoroughly with water for at least fifteen minutes lifting upper and lower lids. Get immediate medical attention.
Skin Contact	Prolonged or repeated exposure may cause a marked skin burn. This material may cause sensitization or allergic response. The acute dermal LD50 is 2000 mg/kg in rabbits. Dermatitis may result from prolonged or repeated skin contact.	Immediately remove contaminated clothing or shoes. Wipe excess from skin and flush with plenty of water for at least 15 minutes. Use soap if available or follow by washing with soap and water. Do not reuse clothing until thoroughly cleaned. Get medical attention. Contaminated leather articles, included shoes, cannot be decontaminated and should be destroyed.
Ingestion	Product may be toxic. May cause severe damage to mouth, throat and stomach. Obtain emergency medical help.	In the event of ingestion, administer 1 glass of water. Do not induce vomiting and get medical help immediately.
Other Health Hazard Information	WARNING - Causes irritation. Avoid contact with skin, eyes and clothing. Overexposure may result in headache, nausea, diarrhea, depression, convulsions, and in serious cases, unconsciousness. This is a skin and eye irritant. This formula contains hazardous fillers which are not hazardous in a wet or encapsulated state. However, if a formula containing a hazardous filler is reduced to a respirable fraction by grinding or putting into an airborne powder, the powder is a hazardous material. May be harmful by inhalation, ingestion or skin absorption, causes irritation. To the best of our knowledge, the chemical, physical and toxicological properties have not been thoroughly investigated.	

SECTION VI - CORROSIVITY AND REACTIVITY DATA

Stability	Stable under normal conditions of storage and handling.	Polymerization may occur <input type="checkbox"/>	Will not occur <input checked="" type="checkbox"/>
Incompatibility (Materials to avoid):	Lewis or mineral acids, bases, oxidizing agents. A reaction accompanied by large heat release occur when the product is mixed with acids.		
Decomposition Products:	By heat and fire: Carbon dioxide, carbon monoxide, Ammonia when heated, Nitrogen oxide in the fire. Nitrogen oxide can react with water vapors to form corrosive nitric acid.		

SECTION VII - ACCIDENTAL RELEASE MEASURES**SPILL OR LEAK PROCEDURES:**

Remove all sources of ignition and ventilate the area. Dike and contain spilled material and control further spillage if feasible. Cover spill with clay, sand, saw dust, vermiculite, Fuller's earth or other suitable absorbent. Collect material in non-leaking containers and seal tightly for disposal.

WASTE DISPOSAL METHOD:

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

SECTION VIII - HANDLING AND STORAGE

STORAGE: Store indoors in a cool dry place away from heat, sparks and flame. Keep containers tightly closed when not in use. Keep away from acids and oxidizers.

SECTION IX - EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Full face shields with goggles underneath. Contact lenses should not be worn.

SKIN PROTECTION: Avoid contact with skin and clothing. Use chemical resistant protective gloves such as neoprene rubber gloves, nitrile rubber gloves, cuffed butyl rubber gloves and other impermeable gloves.

RESPIRATORY PROTECTION: Avoid breathing vapors which may be produced under some conditions such as heating or applications. Avoid breathing aerosols and mists. Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure is excessive. Observe OSHA regulations for respirator use (29 CFR 1910.137).

VENTILATION: General or local ventilation may prove adequate to keep airborne exposures below exposure limits.

SECTION X - REGULATORY INFORMATION

TSCA STATUS: All ingredients in this product are listed in the T.S.C.A. inventory.

CERCLA REPORTABLE QUANTITY: None

SARA TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE:	None
SECTION 311/312 HAZARD CATEGORIES:	None
SECTION 313 TOXIC CHEMICALS:	Contains Bisphenol A, CAS#80-05-7

RCRA:

It is the responsibility of the product user to determine at the time of disposal whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

Although the information and recommendations set forth here in (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof. Wooster Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Wooster Products Inc. be responsible for damages of any nature whatsoever resulting from the use of, or reliance upon information. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose of any other nature are made hereunder with respect to information or the product to which information refers.